JYMPIA Bariatric

The Olympia Bariatric bed combines an exceptional functionality 10550 and a high carrying capacity to support the treatment of bariatric patients.

10550 | Olympia Bariatric

Electric protection class I The bed is earthed by means of the mains cable.

The advantages are:

mechanism.

- An increased ESD (electrostatic discharge) immunity.

The brake pedal is accessible in all bed positions.

The open carriage improves the accessibility under

- A drop in the electromagnetic field.

the bed and the ease of cleaning.

Carriage

- Very stable high/low adjustment by means of a support arm system (lifting capacity of 500 kg).
- Trendelenburg and Reverse Trendelenburg adjustment up to ±15°.
- High quality heavy-duty Twin castors Ø 150 mm with wheel lock.
- Double design pedal to activate the central brake

Mattress platform

- Mattress platform with 4 sections, adjustable in width (91 - 111 - 131).
- The backrest is electrically adjustable up to $\pm 70^{\circ}$ with autoregression.
- The knee rest is electrically adjustable up to ±34°.
- The electric manipulation of the mattress platform section is equipped with a clamp safety.
- Manual quick release of the backrest.
- Battery with alarm signal.
- Mattress platform with solid laminate sections of 6 mm.
- Equipped with cutouts for patients restraint straps.
- Backrest and footrest are equipped with 2 integrated

Electric bed manipulations

- The electric functions can be activated by means of a hand switch, a *mini-nurse box* or a *nurse box* (*).
- The hand switch is equipped with a preprogrammed sleeping function.

- bumpers
- an IV rod or a lifting pole.
- out of 3 different width (104-124-144).
- synthetic accessory hooks.

- A mini-nurse box or a nurse box (*) makes it possible to switch off several functions selectively.

Panel types Sideguards

Atmosphere (*)

Accessoiries

We refer to our extensive accessory list.





- Vela



HAELVOET NV | L. BEKAERTSTRAAT 8, 8770 INGELMUNSTER, BELGIUM | T +32 (0) 51 48 66 95 | F +32 (0) 51 48 73 19 | INFO@HAELVOET.BE | WWW.HAELVOET.BE Since Haelvoet continuously aims to make technological progress, Haelvoet reserves the right to modify the product.



Dimensions and technical data

- Width: 104 124 144 cm, Length: 214 cm
- Height variation of the mattress platform: ± 42 cm - ± 82 cm
- Clearance height: 150 mm
- Safe working load: 500 kg
- Weight (with options): 209 kg
- Mattress platform dimensions: 206 x 91-111-113 cm
- Mattress dimensions: 195 x 90 cm, thickness: 14 to 22 cm



Materials and finishing

- Metal: Epoxy-coating RAL 9006 white aluminium or chrome.
- Solid laminate.
- Hinge points with self-lubricating synthetic bearings (= maintenance-free).
- Withstands the common cleaning products.

For more information about the materials and construction: please consult our material lists. We would to refer to our extensive colour gamut.

Options

- Atmosphere sideguards.
- Nurse box (ACO) + extendible linen holder.
- Illuminated hand switch.
- Nightlight under the bed.

mattress holders.

- Standard with a telescopic bed extension up to +20 cm. Equipotential connection.
- The 4 bed corners are equipped with integrated
- The 4 bed corners are equipped with cases to install
- Bed panel with a solid laminate filling panel, choice
- The side beams on both sides are equipped with 3